

MOTOTRBO™ SL2600

INSTANT COMMUNICATION,
PROFESSIONAL STYLE



GENERAL SPECIFICATIONS

| | | |
|---|------------------------|-------------|
| Model Number | SL2600 | |
| Band | VHF | UHF |
| Frequency | 136-174 MHz | 403-480 MHz |
| High Power Output ¹ (Digital) | 3 W | |
| High Power Output (Analogue) | 2 W | |
| Low Power Output | 0.5, 1W | |
| Channel Spacing | 12.5, 25kHz | |
| Channel Capacity | 256 | |
| Dimensions (H x W x D), Radio + Standard Battery | 125.7 x 55.0 x 22.7 mm | |
| Weight, Radio + Standard Battery | 190g | |
| Digital / Analogue Battery Life ² (Li-Ion (2300mAh) Battery) | 13.5 / 11 hrs | |
| Power Supply (Nominal) | 3.7 V | |

TRANSMITTER SPECIFICATIONS

| | |
|--|---|
| 4FSK Digital Modulation | 12.5 kHz Data: 7K60F1D and 7K60FXD |
| | 12.5 kHz Voice: 7K60F1E and 7K60FXE |
| | Combination of 12.5 kHz Voice and Data: 7K60F1W |
| Digital Protocol | ETSI TS 102 361-1, -2, -3 |
| Conducted/Radiated Emissions (TIA603D) | -36 dBm < 1GHz, -30 dBm > 1GHz |
| Adjacent Channel Power | 60dB (12.5 kHz channel), 70dB (25 kHz channel) |

ADDITIONAL FEATURES

- Transmit Interrupt
- Unified Call List
- Enhanced Privacy
- Fixed Privacy Key Decryption
- Ignore Clear Signal
- Bluetooth Audio
- Bluetooth Data
- Indoor Location
- Emergency Search Tone
- Covert Mode
- Intelligent Audio
- Mute Mode
- Noise Suppressor
- Notification List
- Radio Service Menu
- Quick Text Messaging
- User-Selectable Audio Profiles

RECEIVER SPECIFICATIONS

| | |
|--|--|
| Analogue Sensitivity (12dB SINAD) | 0.3 uV, 0.22uV (typical) |
| Digital Sensitivity (5% BER) | 0.25 uV, 0.19uV (typical) |
| Intermodulation (TIA603D) | 70 dB |
| Adjacent Channel Selectivity, (TIA603A)-1-tone | 60 dB (12.5 kHz channel), 70 dB (25 kHz channel) |
| Adjacent Channel Selectivity, (TIA603D)-2-tone | 45 dB (12.5 kHz channel), 70 dB (25 kHz channel) |
| Spurious Rejection (TIA603D) | 70 dB |



AUDIO SPECIFICATIONS

| | |
|--|--|
| Digital Vocoder Type | AMBE+2™ |
| Audio Response | TIA603D |
| Rated Audio | 0.5 W |
| Audio Distortion at Rated Audio | 5% (3% typical) |
| Hum and Noise | -40 dB (12.5 kHz channel) -45 dB (25 kHz channel) |
| Conducted Spurious Emissions (TIA603D) | -57 dBm |

BLUETOOTH SPECIFICATIONS

| | |
|-----------------------------|---|
| Version | 4 |
| Range | Class 2, 33 ft (10 m) |
| Supported Profiles | Bluetooth Headset Profile (HSP), Serial Port Profile (SPP), Motorola fast push-to-talk. |
| Simultaneous Connections | 1 x audio accessory and 1 x data device |
| Permanent Discoverable Mode | Optional |

ENVIRONMENTAL SPECIFICATIONS

| | |
|------------------------------------|---------------------------------|
| Operating Temperature ³ | -30 C to +60 C (-22 F to 140 F) |
| Storage Temperature | -40 C to +85 C (-40 F to 185 F) |
| Electrostatic Discharge | IEC 61000-4-2 Level 3 |
| Dust and Water Intrusion | IEC 60529 - IP54 |
| Packaging Test | MIL-STD 810D and E |

WiFi SPECIFICATIONS

| | |
|-----------------------------|--------------------------------|
| Standards Supported | IEEE 802.11b, 802.11g, 802.11n |
| Security Protocol Supported | WPA, WPA-2, WEP |
| Maximum Number of SSIDs | 128 |

MILITARY STANDARDS

| | 810C | | 810D | | 810E | | 810F | | 810G | |
|--------------------|---------|--------------------------|---------|---------------------|---------|---------------------|---------|---------------------|---------|---------------------|
| | Methods | Procedures | Methods | Procedures | Methods | Procedures | Methods | Procedures | Methods | Procedures |
| Applicable MIL-STD | 500.1 | I | 500.2 | II | 500.3 | II | 500.4 | II | 500.5 | II |
| Low Pressure | 501.1 | I, II | 501.2 | I/A1, II/A1 | 501.3 | I/A1, II/A1 | 501.4 | I/Hot, II/Hot | 501.5 | I/A1, II/A1 |
| High Temperature | 502.1 | I | 502.2 | I/C3, II/C1 | 502.3 | I/C3, II/C1 | 502.4 | I/C3, II/C1 | 502.5 | I/C3, II/C1 |
| Low Temperature | 503.1 | I | 503.2 | A1/C3 | 503.3 | A1/C3 | 503.4 | I | 503.5 | I-C |
| Temperature Shock | 505.1 | II | 505.2 | I/Hot-Dry | 505.3 | I/Hot-Dry | 505.4 | I/Hot-Dry | 505.5 | I/A1 |
| Solar Radiation | 506.1 | I, II | 506.2 | I, II | 506.3 | I, II | 506.4 | I, III | 506.5 | I, III |
| Rain | 507.1 | II | 507.2 | II/Hot-Humid | 507.3 | II/Hot-Humid | 507.4 | - | 507.5 | II - Aggravated |
| Humidity | 509.1 | I | 509.2 | I | 509.3 | I | 509.4 | - | 509.5 | - |
| Salt fog | 510.1 | I | 510.2 | I | 510.3 | I | 510.4 | I | 510.5 | I |
| Dust | - | - | 510.2 | II | 510.3 | II | 510.4 | II | 510.5 | II |
| Sand | 514.2 | VIII/CatF/ CurveW, XI | 514.3 | I/Cat10, II/Cat3 | 514.4 | I/Cat10, II/Cat3 | 514.5 | I/Cat24, II/Cat5 | 514.6 | I/Cat24, II/Cat5 |
| Vibration | 516.2 | I, II | 516.3 | I, IV | 516.4 | I, IV | 516.5 | I, IV | 516.6 | I, IV, V, VI |
| Shock | | | | | | | | | | |

1: Radio frequency > 470MHz only 2W for Digital.

2: Typical battery life, 5/5/90 profile at maximum transmitter power with Bluetooth and Wi-Fi disabled. Actual observed runtimes may vary.

3: Radio only. Operating temperature specification for a Li-Ion battery is -10 C to +60 C.

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, UK.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2017 Motorola Solutions, Inc. All rights reserved. EMEAv1 (09/17)



Distributed by:

Direct Communications Radio Services Ltd
 HQ | Edison Road
 St Ives
 CAMBS
 PE27 3LH
 Call: 0800 043 2688
 www.mototrbo.co.uk | sales@dcrs.co.uk

